OBJY2.E194304 Systems, Electrical Insulation - Component

Page Bottom

Systems, Electrical Insulation - Component

See General Information for Systems, Electrical Insulation - Component

NERI MOTORI SRL E194304

VIA FLEMING 6/8

40017 S GIOVANNI PERSICETO, BO ITALY

Class 155(F) insulation system, designated F, 600V.

Class 155(F) insulation system, designated F2, 600V.

Class 180(H) insulation system, designated H, 600V.

Class 180(H) insulation system, designated H2, 600V.

Marking: Company name and system designation.

Last Updated on 2003-04-29

Questions? Notice of Disclaimer Page Top

Copyright © 2007 Underwriters Laboratories Inc.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of th data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2007 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



OBJY8.E194304 Systems, Electrical Insulation Certified for Canada - Component

Page Bottom

Systems, Electrical Insulation Certified for Canada - Component

See General Information for Systems, Electrical Insulation Certified for Canada - Component

NERI MOTORI SRL E194304

VIA FLEMING 6/8

40017 S GIOVANNI PERSICETO, BO ITALY

Class 155(F) insulation system , designated F, 600V.

Class 155(F) insulation system , designated F2, 600V.

Class 180(H) insulation system, designated H, 600V.

Class 180(H) insulation system, designated H2, 600V.

Marking: Company name, trademark, system designation and Recognized Component Mark for Canada $oldsymbol{c}$

Last Updated on 2003-12-03

Questions?

Notice of Disclaimer Page Top

Copyright © 2007 Underwriters Laboratories Inc.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of th data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2007 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



PRGY2.E201235 Motors - Component

Page Bottom

Motors - Component

See General Information for Motors - Component

NERI MOTORI SRL E201235

VIA FLEMING 6/8 40017 S GIOVANNI PERSICETO, BO ITALY

Single and three phase squirrel cage induction motor, Series T, M, DP, AT, MD, AM, AD, AP, MV, AV, MC, CD, CV, CM, CP, CA followed b 50, 56, 63, 71, 80, 90, 100, 112, 132, 160, 180, 200 may be followed by A, B, C, or D, may be followed by S, M, L, LA, LB or ML, followed by 2, 4, 6, 8, 10, 12, 16, 32, 2/4, 2/6, 2/8, 2/10, 2/12, 2/16, 4/6, 4/8, 4/10, 4/12, 4/16, 4/32 6/8, 6/10, 6/12, 8/10, or 8/12, may be followed bo B3, B5 or B14; rated max 600 Vac at 50Hz and 60Hz, or 50Hz/60Hz, output from 0.03 kW to 45 kW max, multi speed, with ambient temperature 40[ordm]C. Totally enclosed fan cooled (TEFC) or totally enclosed non ventilated (TENV) or air over motor (TEAO). Marking: Company name or "E201235", date code and motor series designation.

Last Updated on 2006-10-31

Questions? Notice of Disclaimer Page Top

Copyright © 2007 Underwriters Laboratories Inc.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of th data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2007 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



PRGY8.E201235 Motors Certified for Canada - Component

Page Bottom

Motors Certified for Canada - Component

See General Information for Motors Certified for Canada - Component

NERI MOTORI SRL E201235

VIA FLEMING 6/8 40017 S GIOVANNI PERSICETO, BO ITALY

Single and three phase squirrel cage induction motor, Series T, M, DP, AT, MD, AM, AD, AP, MV, AV, MC, CD, CV, CM, CP, CA followed b 50, 56, 63, 71, 80, 90, 100, 112, 132, 160, 180, 200 may be followed by A, B, C, or D, may be followed by S, M, L, LA, LB or ML, followed by 2, 4, 6, 8, 10, 12, 16, 32, 2/4, 2/6, 2/8, 2/10, 2/12, 2/16, 4/6, 4/8, 4/10, 4/12, 4/16, 4/32 6/8, 6/10, 6/12, 8/10, or 8/12, may be followed bo B3, B5 or B14; rated max 600 Vac at 50Hz and 60Hz, or 50Hz/60Hz, output from 0.03 kW to 45 kW max, multi speed, with ambient temperature 40[ordm]C. Totally enclosed fan cooled (TEFC) or totally enclosed non ventilated (TENV) or air over motor (TEAO).

Marking: Company name or "E201235", motor series designation, date code and the Recognized Component Mark for Canada, \mathbf{c} <u>Last Updated</u> on 2006-10-31

<u>Questions?</u> <u>Notice of Disclaimer</u> <u>Page Top</u>

Copyright © 2007 Underwriters Laboratories Inc.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of th data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2007 Underwriters Laboratories Inc.®"

 $An \ independent \ organization \ working \ for \ a \ safer \ world \ with \ integrity, \ precision \ and \ knowledge.$

