



















5.9 **Momenti d'inerzia** [Kg·cm²]
(riferiti all'albero veloce in entrata)


5.9 **Moments of inertia** [Kg·cm²]
(referred to input shaft)

5.9 **Trägheitsmoment** [Kg·cm²]
(bez. Antriebswelle)

	in	RA 	RC 				RF 			
			IEC B5				IEC B5			
			63	71	80	90	63	71	80	90
S 	1	4.53	-	-	5.09	5.11	4.81	5.31	5.44	6.51
	2.5	0.88	0.93	1.07	1.45	1.50	1.13	1.15	1.82	2.89
	5	0.36	0.41	0.55	0.93	0.97	0.61	0.63	1.31	2.37
	10	0.19	0.22	0.36	0.74	0.79	0.44	0.46	1.14	2.20
19 B 	1	4.57	-	-	5.13	5.14	4.84	5.34	5.48	6.55
	2.5	0.88	0.93	1.07	1.45	1.50	1.13	1.15	1.83	2.89
	5	0.36	0.41	0.55	0.93	0.97	0.61	0.63	1.31	2.37
	10	0.19	0.22	0.36	0.74	0.79	0.44	0.46	1.14	2.20
C 	1	4.17	-	-	4.74	4.80	4.45	4.95	5.08	6.16

	in	RA 	RC 				RF 			
			IEC B5				IEC B5			
			71	80	90	110-112	71	80	90	110-112
S 	1	11.52	-	-	12.37	13.22	13.36	13.69	13.61	15.39
	2.5	2.46	2.87	3.04	3.42	4.26	3.32	3.46	4.63	6.80
	5	1.08	1.45	1.62	2.00	2.84	1.94	2.07	3.25	5.42
	10	0.64	0.97	1.14	1.52	2.36	1.49	1.63	2.80	4.97
24 B 	1	11.60	-	-	12.46	13.31	13.45	13.77	13.70	15.47
	2.5	2.47	2.88	3.05	3.43	4.27	3.33	3.47	4.64	6.81
	5	1.08	1.45	1.62	2.00	2.84	1.94	2.07	3.25	5.42
	10	0.64	0.97	1.14	1.52	2.36	1.49	1.63	2.80	4.97
C 	1	10.48	-	-	11.33	12.18	12.32	12.64	12.57	14.34

	in	RA 	RC 				RF 			
			IEC B5				IEC B5			
			80	90	110-112	132	80	90	110-112	132
S 	1	31.45	-	-	33.06	36.42	35.79	35.74	35.91	46.94
	2.5	7.02	7.95	7.82	8.78	11.92	9.36	9.29	11.60	25.60
	5	3.22	4.06	3.93	4.88	8.02	5.55	5.48	7.80	21.79
	10	1.75	2.46	2.33	3.28	6.42	4.08	4.01	6.33	20.32
28 B 	1	31.87	-	-	33.49	36.84	36.21	36.16	36.34	47.36
	2.5	7.05	7.98	7.85	8.80	11.94	9.38	9.31	11.63	25.62
	5	3.23	4.06	3.93	4.88	8.02	5.56	5.49	7.81	21.80
	10	1.75	2.46	2.33	3.28	6.42	4.08	4.01	6.33	20.33
C 	1	28.36	-	-	29.97	33.33	32.69	32.65	32.82	43.84



5.9 **Momenti d'inerzia** [Kg·cm²]
(riferiti all'albero veloce in entrata)

5.9 **Moments of inertia** [Kg·cm²]
(referred to input shaft)

5.9 **Trägheitsmoment** [Kg·cm²]
(bez. Antriebswelle)

		i_n	RA	RC						RF					
				IEC B5						IEC B5					
				80	90	110-112	132	160	180	80	90	110-112	132	160	180
38		1	82.73	-	-	-	86.77	91.21	94.03	-	99.4	100.4	101.8	103.9	149.0
		2.5	20.67	21.83	21.70	21.84	25.04	29.46	32.48	22.87	25.25	25.43	40.29	42.47	87.73
		5	7.92	8.95	8.82	8.95	12.15	16.58	19.60	10.12	12.50	12.67	27.53	29.71	74.98
		10	4.17	4.83	4.70	4.84	8.04	12.46	15.48	6.36	8.75	8.92	23.78	25.96	71.23
38		1	84.86	-	-	-	88.91	93.34	96.16	-	101.49	102.53	103.90	106.08	151.18
		2.5	20.74	21.90	21.77	21.91	25.11	29.53	32.55	22.94	25.32	25.49	40.35	42.53	87.80
		5	7.94	8.96	8.83	8.97	12.17	16.60	19.61	10.13	12.52	12.69	27.55	29.73	75.00
		10	4.17	4.83	4.70	4.84	8.04	12.47	15.48	6.37	8.75	8.93	23.79	25.97	71.23
38		1	76.44	-	-	-	80.58	85.01	87.84	-	16.63	17.67	19.04	21.22	66.32

		i_n	RA	RC						RF				
				IEC B5						IEC B5				
				110-112	132	160	180	200	110-112	132	160	180	200	
48		1	177.58	177.7	183.4	182.4	185.3	195.7	233.7	238.9	246.9	244.9	241.4	
		2.5	61.86	64.36	70.04	69.04	71.95	82.34	81.5	82.8	85.0	134.1	130.7	
		5	24.06	26.80	32.48	31.48	34.39	44.78	43.7	45.0	47.2	96.3	92.9	
		10	11.50	13.77	19.45	18.45	21.36	31.75	31.1	32.5	34.7	83.8	80.3	
48		1	183.40	183.5	189.2	188.2	191.1	201.5	239.5	244.7	252.7	250.7	247.2	
		2.5	62.11	64.70	70.38	69.38	72.29	82.68	81.7	83.1	85.3	134.4	130.9	
		5	24.13	26.89	32.57	31.57	34.48	44.87	43.7	45.1	47.3	96.4	92.9	
		10	11.52	13.80	19.48	18.48	21.39	31.77	31.1	32.5	34.7	83.8	80.3	
48		1	160.10	160.8	166.5	165.5	168.4	178.8	-	221.4	229.4	227.4	223.9	